

CHECKLIST · TOMORIS TOOLBOX

Backup Checklist: 3-2-1-1-0 with an Offline Copy and Tested Recovery

A data backup checklist, backed by BSI IT-Grundschutz CON.3, the BSI Ransomware Measures Catalog, and CISA

UPDATED

Oct 22, 2026

LENGTH

PDF, 5 pages

ONLINE

tomoris.com/en/downloads/backup-checkliste-3-2-1-1-0

AT A GLANCE

3-2-1-1-0

Rule with an offline copy and tested recovery

19

Checkpoints to tick off, each with a source

1× a year

Minimum recovery test (CISA CPG 2.0)

WHO IT IS FOR

- Executives and IT managers in small and medium-sized businesses
- Administrators who run or set up backups
- Anyone who has outsourced backups to a service provider and wants to check them

WHAT THIS COVERS

According to the US agency CISA, most ransomware attackers try to find reachable backups and delete or encrypt them. This checklist turns the 3-2-1 rule and its extension with an offline copy and verified recovery into items you can check off. It is based on module CON.3 Data Backup Concept of the BSI IT-Grundschutz Compendium, the BSI Ransomware Measures Catalog, and CISA recommendations.

This checklist summarizes the requirements and recommendations of the bodies named and does not replace a backup concept. Which frequency, retention, and recovery time suit your systems depends on your business processes.

CONTENTS

01	The Rule: 3-2-1-1-0	2
02	Concept and Plans	3
03	Store Separately and Securely	3
04	Test Recovery: Zero Errors	4
05	Sources	5

01

The Rule: 3-2-1-1-0

What the five digits mean and which body recommends which part.

3

Copies

Three copies of important data: the original and two backups (BSI aid for Standard 200-4, ENISA, CISA).

2

Storage media

On two different storage media (BSI aid for Standard 200-4, ENISA, CISA).

1

Copy at another location

One copy at another location, physically separated, ideally in a different fire compartment (BSI CON.3.A12, ENISA, CISA).

1

Copy offline

One copy offline: disconnected from all other systems after the backup (BSI Ransomware Measures Catalog, CISA #StopRansomware Guide).

0

Errors during recovery

Zero errors: recovery is tested, and the data comes back intact and on time (BSI CON.3.A15, CISA CPG 2.0).

3-2-1 is recommended by the BSI (aid for BCM Standard 200-4), the EU agency ENISA, and the US agency CISA. The extension to 3-2-1-1-0 is not a standard but a term coined by vendors. However, BSI and CISA explicitly recommend its two additions, an offline copy and verified recovery.

Data mirroring via RAID does not count as a backup (BSI CON.3, description). For entities covered by NIS2, backup management is explicitly one of the risk management measures (§ 32 para. 4 lit. c NISG 2026 (Austrian Network and Information Systems Security Act 2026)).

02 —

Concept and Plans

What is backed up, how often, for how long, and in which order it comes back.

- ☐ The framework conditions are recorded for every system: data to be backed up, storage and change volume, availability, confidentiality, legal requirements, deletion rules, and responsibilities (CON.3.A1).
- ☐ The type, frequency, and timing of backups are defined, as are storage media, transport, and retention (CON.3.A2).
- ☐ There is a backup plan for each system or group of systems: what is backed up, recovery order, procedure, retention period, protection against access and overwriting, and the hardware and software used (CON.3.A4).
- ☐ For every system, the maximum tolerable data loss is defined (Recovery Point Objective, CON.3.A6).
- ☐ The recovery plans are available even if the backup system itself fails, for example also on paper (CON.3.A6; threat 2.4 cites ransomware as the reason).
- ☐ All employees know the backup rules and their own tasks in them (CON.3.A5).
- ☐ Online storage is governed by contract: storage location, availability, sign-in, and encryption of stored and transmitted data (CON.3.A9).

03 —

Store Separately and Securely

Dedicated media, another location, one copy offline, and no overwriting by unauthorized parties.

- ☐ Backups are always stored on dedicated storage media, not only on the system being backed up (CON.3.A2).
- ☐ The media are stored physically separated from the backed-up systems, ideally in a different fire compartment (CON.3.A12).
- ☐ At least one copy is offline and disconnected from all other systems after the backup (BSI Ransomware Measures Catalog; CON.3.A2 for media requiring special protection).

- ☐ Separation test: a domain administrator tries to access the separated copies as a test. This must fail (BSI Ransomware Measures Catalog).
- ☐ Backups cannot be overwritten, either intentionally or by accident; only authorized backup and administration processes have write access (CON.3.A14).
- ☐ Backups are encrypted, the keys are backed up separately, and encrypted data can still be restored even after a long time (CON.3.A13, for elevated protection needs).

Automatic synchronization to the cloud is not an adequate backup on its own: if an attacker encrypts the local files, the encrypted versions are synchronized as well (CISA #StopRansomware Guide).

04

Test Recovery: Zero Errors

Regularly, at least once a year, completely, and within a reasonable time.

- ☐ Regular tests check whether backed-up data can be restored intact and within a reasonable time (CON.3.A15).
- ☐ Recovery is tested at least once a year (CISA CPG 2.0; WKO guide on technical and organizational measures).
- ☐ The recovery of data and entire systems is practiced, not just the backup (BSI Ransomware Measures Catalog).
- ☐ The recovery order follows the importance of the services (CON.3.A4; CISA #StopRansomware Guide).
- ☐ Regular checks confirm that the backup concept is implemented as described (CON.3.A6).
- ☐ The result and duration of every test are documented; errors are fixed and tested again.

The last item is a TOMORIS recommendation: only a documented, successful test shows that the zero in 3-2-1-1-0 has been achieved.

NEXT STEP

Check It Yourself or Put It into Practice Together

DISCUSS IMPLEMENTATION

Get in Touch

tomoris.com/en/contact

contact@tomoris.com

05

Sources

All statements are supported by sources. Legislation applies in its current version.

- 1 **BSI IT-Grundschutz Compendium, module CON.3 Data Backup Concept, 2023 edition**
Requirements A1, A2, A4, A5, A6, A9, A12 to A15, threats 2.4 and 2.10
www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Grundschutz/IT-GS-K...
- 2 **BSI: Ransomware Measures Catalog, version 1.0 of February 23, 2022**
Offline copy, separation test, practicing recovery
www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Cyber-Sicherheit/Th...
- 3 **BSI: Proposals for Business Continuity Strategies, aid for BSI Standard 200-4 (Community Draft 2.0)**
Chapter 3.1, 3-2-1 rule
www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Grundschutz/Hilfsmi...
- 4 **ENISA: Threat Landscape for Ransomware Attacks (July 2022)**
Chapter 6.1
www.enisa.europa.eu/sites/default/files/publications/ENISA%20Th...
- 5 **CISA: #StopRansomware Guide**
Offline and encrypted backups, cloud synchronization, recovery by priority
www.cisa.gov/resources-tools/resources/stopransomware-guide
- 6 **CISA: Cross-Sector Cybersecurity Performance Goals 2.0**
Offline backups, test at least once a year
www.cisa.gov/cybersecurity-performance-goals-2-0-cpg-2-0
- 7 **CISA/US-CERT: Data Backup Options**
3-2-1 rule
www.cisa.gov/sites/default/files/publications/data_backup_optio...
- 8 **WKO it-safe: Guide to technical and organizational measures under the GDPR**
Section 3.7, annual recovery test
www.wko.at/oe/it-sicherheit/leitfaden-massnahmen-dsgvo-1.pdf
- 9 **NISG 2026, BGBl. I No. 94/2025, § 32 para. 4 lit. c**
www.ris.bka.gv.at/eli/bgbli/i/2025/94
- 10 **Veeam: 3-2-1 Backup Rule (origin of the term 3-2-1-1-0)**
www.veeam.com/blog/321-backup-rule.html